



QUALITY PLUS  
HIGH PERFORMANCEQUA  
HIGH

# MS LACQUER

Caslek MS Lacquer is an acrylic Lacquer with medium solids content offering a flawless mirror-like finish. It is easy to apply, fast drying, and has an excellent gloss level.

## TECHNICAL INFORMATION

	<b>Substrates</b>	Caslek MS Lacquer can be applied over solvent-based basecoat and properly prepared paint work in good conditions.						
	<b>Mixing ratio</b>	<table border="1" data-bbox="710 1136 1107 1233"> <tr> <td>MS Lacquer</td><td>:</td><td>Hardener</td></tr> <tr> <td>2</td><td>:</td><td>1</td></tr> </table>	MS Lacquer	:	Hardener	2	:	1
MS Lacquer	:	Hardener						
2	:	1						
	<b>Pot life</b>	With hardener, 3 hours at 23°C						
	<b>Spray gun tips</b>	Spray gun: 1.3 mm Conventional: 3.0-3.5 bar/45-50 psi inlet HVLP: 2 bar/26-30 psi inlet						
	<b>Spray method</b>	Application Viscosity: 16-18 seconds – DIN Cup 4 at 23°C Coats & Thickness: 2-3 coats, total 40-60um Flash-Off Time: At 23°C, 5-10 minutes between coats						

N

1.

2

3

4

03-A