

# G3 Regular Grade







Paste Compound

# Farécia G3 REGULAR GRADE POMPOUND PASTE COMPOUND AXISTORIA AXISTORIA COMPOUND AXISTORIA AXISTORIA COMPOUND AXISTORIA AXISTO

## Product Description

G3 Regular Grade Paste Compound is recommended for use on OEM and refinish paint systems.

This versatile product can be used by hand or machine. Use with a G Mop 6" Wet Use Compounding Foam (GMC606) for ease of use and low splatter.

### **Product Information**

Size	Code	Ctn Qty
250g	G3-250	24
400g	G3-400	12
1kg	G3-1000	12
3kg	G3-3000	4

Key Benefits	
Reliable Cut	Removes P1500 or finer abrasive marks quickly and easily
Permanent Finish	Contains no fillers so scratch marks will not reappear
• High Gloss System	Excellent gloss. Can be used with G3 Fine Finishing Compound for an enhanced gloss finish on dark colours
• Silicone Free	100% paintshop safe



### Use With

### **Machine Application**



G Mop 6" Wet Use Compounding Foam GMC606



G Mop Flexible Back Plate for 6" Pads GMB146 (14mm thread) GMB586 (5/8" thread)

GMB166 (16mm thread)



Water Spray Bottle WSB (600ml)



Farécla Finishing Cloth FC-3 (3 x cloths)

### How To Use

### **Machine Application**



Soak a G Mop 6" Wet Use Compounding Foam



Attach pad to the polishing machine, spin off excess water and knead



Knead tube or mix compound well, then apply to pad or surface



Spread and compound at 1500 - 1800rpm. Apply more water if necessary



Wipe clean with Finishing Cloth


### **Hand Application**



Soak and rinse out a Finishing Cloth



Knead tube or mix compound well, then apply to cloth or surface



Rub product on the surface in a back and forth motion



Apply water if necessary. Wipe clean with Finishing Cloth

### **Technical Information**

Appearance: White coloured paste

Viscosity: **Highly viscous** VOC Content: **177g/L** Relative Density: **1.44** 

pH: 9 - 10

Paint Type Compliance: MS & HS

